

Tapered roller bearing 740R-742-JTEKT - 740R-742-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/740r-742-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_a max.	r_b max.	C_r	C_{10}	Grease lub.	Oil lub.
80.962	150.089	44.450	46.672	30.512	5.2	3.2	264	368	2 500	3 400

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer to) Mass (kg)		
Inner ring	Outer ring	a	d_a	d_b	D_a	D_b	r_a max.	r_b max.	e	Y_1	Y_2	Inner ring	Outer ring
740R	742	32.4	101.0	91.0	134.0	142.0	5.2	3.2	0.33	1.84	1.01	2.30	1.06

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250202797
Inside diameter	80.962 mm
Outside diameter	150.089 mm
Thickness	44.45 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE