

Tapered roller bearing 750AR-742-JTEKT - 750AR-742-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/750ar-742-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)			Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁ max.	r ₁ min.	C _r	C ₁₀	Grease lub.	Oil lub.	
82.550	150.089	44.450	46.672	38.512	6.7	3.2	264	388	2 500	3 400	

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to) Mass (kg)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
750AR	742	32.4	106.0	93.0	134.0	142.0	6.7	3.2	0.33	1.84	1.01	2.19	1.06

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952429397
Inside diameter	82.55 mm
Outside diameter	150.089 mm
Thickness	44.45 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE