

## Tapered roller bearing 677-672-JTEKT - 677-672-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/677-672-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub> max.	r <sub>1</sub> min.	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.
85.725	168.275	41.275	41.275	30.162	3.6	3.2	224	349	2 200	3 000

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer to) Mass (kg)		
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
677	672	38.6	105.0	99.0	149.0	160.0	3.6	3.2	0.47	1.28	0.70	2.89	1.22

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952429564
Inside diameter	85.725 mm
Outside diameter	168.275 mm
Thickness	41.275 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE