

## Tapered roller bearing 98350-98788-JTEKT - 98350-98788-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/98350-98788-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub> max.	r <sub>1</sub> min.	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.
88.900	200.000	52.761	49.212	34.925	3.6	3.2	347	471	1 400	1 900

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Con-stant	Axial load factors		(Refer) Mass (kg)	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
98350	98788	54.5	118.0	112.0	174.0	168.0	3.6	3.2	0.83	0.95	0.52	5.27	2.28

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952429700
Inside diameter	88.9 mm
Inside diameter	3 1/2" inch
Outside diameter	200 mm
Outside diameter	7.874" inch
Thickness	52.761 mm
Thickness	2.077" inch
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE