


# Tapered roller bearing

## JM718149-JM718110-JTEKT - JM718149-JM718110-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/jm718149-jm718110-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)								Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub>	r <sub>2</sub>	r <sub>3</sub>	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.	
90.000	145.000	35.000	34.000	27.000	3.0	2.5		194	291	2 500	3 400	

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
JM718149	JM718110	32.7	105.0	99.0	131.0	139.0	3.0	2.5	0.44	1.35	0.74	1.47	0.652

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952429717
Inside diameter	90 mm
Outside diameter	145 mm
Thickness	35 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE