

Tapered roller bearing HH224334-HH224310-JTEKT - HH224334-HH224310-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/hh224334-hh224310-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_a max.	r_b max.	C_r	C_{10}	Grease lub.	Oil lub.
99.975	212.725	66.675	66.675	53.975	3.6	3.2	513	699	1 800	2 400

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer to) Mass (kg)		
Inner ring	Outer ring	a	d_a	d_b	D_a	D_b	r_a max.	r_b max.	e	Y_1	Y_2	Inner ring	Outer ring
HH224334	HH224310	47.6	122.0	117.0	192.0	202.0	3.6	3.2	0.33	1.84	1.01	7.91	3.03

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952429892
Inside diameter	99.975 mm
Outside diameter	212.725 mm
Thickness	66.675 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE