

Tapered roller bearing HH224335-HH224310-JTEKT - HH224335-HH224310-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/hh224335-hh224310-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)			Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁	r ₂	C _r	C ₁₀	Grease lub. Oil lub.		
101.600	212.725	66.675	66.675	53.975	7.1	3.2	513	699	1 800	2 400	

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to Mass (kg))	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
HH224335	HH224310	47.6	121.0	134.0	189.0	201.0	7.1	3.2	0.33	1.84	1.01	7.76	3.03

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952430003
Inside diameter	101.6 mm
Outside diameter	212.725 mm
Thickness	66.675 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE