

Tapered roller bearing 936-932-JTEKT - 936-932-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/936-932-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	d _a	d _b	C _r	C ₁₀	Grease lub.	Oil lub.
107.950	212.725	66.675	66.675	52.975	7.9	3.2	450	674	1 800	2 400

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer) Mass (kg)		
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
936	932	47.6	137.0	122.0	187.0	193.0	7.9	3.2	0.33	1.84	1.01	6.52	4.07

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952430126
Inside diameter	107.95 mm
Inside diameter	4 1/4" inch
Outside diameter	212.725 mm
Outside diameter	8 3/8" inch
Thickness	66.675 mm
Thickness	2 5/8" inch
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE