

Tapered roller bearing LM522548-LM522510-JTEKT - LM522548-LM522510-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/lm522548-lm522510-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁ max.	r ₁ min.	C _r	C ₁₀	Grease lub.	Oil lub.
109.987	159.987	34.925	34.925	20.988	7.9	3.2	184	319	2 200	2 900

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to Mass (kg))	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
LM522548	LM522510	32.9	131.0	121.0	146.0	153.0	7.9	3.2	0.40	1.50	0.82	1.52	0.784

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952430157
Inside diameter	109.987 mm
Outside diameter	159.987 mm
Thickness	34.925 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE