

## Tapered roller bearing 64450R-64700-JTEKT - 64450R-64700-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/64450r-64700-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub> max.	r <sub>1</sub> min.	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.
114.300	177.800	41.275	41.275	30.162	3.6	3.2	234	380	2 000	2 700

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer) Mass (kg)	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
64450R	64700	42.8	131.0	125.0	160.0	172.0	3.6	3.2	0.52	1.16	0.64	2.45	1.10

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952430270
Inside diameter	114.3 mm
Outside diameter	177.8 mm
Thickness	41.275 mm
Weight	3550 g
Packaging	-
Standard	-

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE