


Tapered roller bearing HH926744-HH926710-JTEKT - HH926744-HH926710-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/hh926744-hh926710-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)								Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_a max.	r_b max.	C_r	C_{10}	Grease lub.	Oil lub.	
114.300	273.050	82.550	82.550	53.975	6.4	6.4	707	898	1 500	1 900	

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to) Mass (kg)	
Inner ring	Outer ring	a	d_a	d_b	D_a	D_b	r_a max.	r_b max.	e	Y_1	Y_2	Inner ring	Outer ring
HH926744	HH926710	76.1	133.0	151.0	230.0	252.0	6.4	6.4	0.83	0.95	0.52	15.0	6.97

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952430393
Inside diameter	114.3 mm
Outside diameter	273.05 mm
Thickness	82.55 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE