

Tapered roller bearing HH224349-HH224310-JTEKT - HH224349-HH224310-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/hh224349-hh224310-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r_a</i>	<i>r_b</i>	<i>C_r</i>	<i>C_{0r}</i>	Grease lub.	Oil lub.
114.976	212.725	66.675	66.675	53.975	7.1	3.2	513	699	1 800	2 400

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer to) Mass (kg)		
Inner ring	Outer ring	<i>a</i>	<i>d_a</i>	<i>d_b</i>	<i>D_a</i>	<i>D_b</i>	<i>r_a</i> max.	<i>r_b</i> max.	<i>e</i>	<i>Y₁</i>	<i>Y₂</i>	Inner ring	Outer ring
HH224349	HH224310	47.6	135.0	134.0	189.0	201.0	7.1	3.2	0.33	1.84	1.01	6.58	3.03

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952430416
Inside diameter	114.9 mm
Outside diameter	212.725 mm
Thickness	66.675 mm
Weight	9850 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE