

Tapered roller bearing HH228340-HH228310-JTEKT - HH228340-HH228310-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/hh228340-hh228310-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	d_a max.	d_b min.	C_r	C_{10}	Grease lub.	Oil lub.
120.650	254.000	77.788	82.560	61.912	9.5	6.4	717	1 050	1 500	2 000

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer) Mass (kg)		
Inner ring	Outer ring	a	d_a	d_b	D_a	D_b	r_a max.	r_b max.	e	Y_1	Y_2	Inner ring	Outer ring
HH228340	HH228310	54.3	158.0	142.0	223.0	234.0	9.5	6.4	0.32	1.87	1.03	12.6	6.00

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952430478
Inside diameter	120.65 mm
Inside diameter	4 3/4" inch
Outside diameter	254 mm
Outside diameter	10" inch
Thickness	77.788 mm
Thickness	3 1/16" inch
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE