

# Tapered roller bearing L540049-L540010-JTEKT - L540049-L540010-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/l540049-l540010-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)						Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )	
$d$	$D$	$T$	$B$	$C$	$r_a$ max.	$r_b$ max.	$C_r$	$C_{10}$	Grease lub.	Oil lub.
196.850	254.000	28.575	27.783	21.433	1.6	1.6	188	387	1 200	1 600

  

Bearing No.		Load center (mm) $a$	Mounting dimensions (mm)						Constant $e$	Axial load factors		(Refer to Mass (kg))	
Inner ring	Outer ring		$d_a$	$d_b$	$D_a$	$D_b$	$r_a$ max.	$r_b$ max.		$Y_1$	$Y_2$	Inner ring	Outer ring
L540049	L540010	43.1	206.0	214.0	238.0	243.0	1.6	1.6	0.40	1.51	0.83	2.34	1.02

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952431772
Inside diameter	196.85 mm
Outside diameter	254 mm
Thickness	28.575 mm
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE