

## Needle roller bearing 16BTM2212A-JTEKT - 16BTM2212A-JTEKT

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/16btm2212a-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_0$	$C_{0r}$	Oil lub.	Caged type With open ends    With closed end
16	22	12	9.3	7.80	9.80	22 000	16BTM2212A

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	15.989	16.000	21.991 <sup>4)</sup>	22.012 <sup>4)</sup>	11	12

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952470283
Inside diameter	16 mm
Outside diameter	22 mm
Thickness	12 mm
Weight	11 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE