

## Needle roller bearing MKM162414U-JTEKT - MKM162414U-JTEKT

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/mkm162414u-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>2)</sup>	
$F_w$	$D$	$C$	$b$ min.	$C_0$	$C_{0r}$	Oil lub.	Oil lub.	Caged type With open ends    With closed end
16	24.15	14	12.6	8.45	9.05	12 000 <sup>1)</sup>		<b>MKM162414U</b>

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	15.989	16.000	24.122	24.143	—	19

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952470382
Inside diameter	16 mm
Outside diameter	24.15 mm
Thickness	14 mm
Weight	19 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE