

Needle roller bearing BHTM1920-JTEKT - BHTM1920-JTEKT

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/bhtm1920-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | Bearing No. ²⁾ | |
|--------------------------|-----|-----|-------------------------|-------|--------------------------------------|----------|---------------------------|-----------------|
| F_w | D | C | b min. | C_0 | C_{0r} | Oil lub. | Caged type | |
| | | | | | | | With open ends | With closed end |
| 19 | 27 | 20 | — | 17.0 | 23.4 | 18 000 | BHTM1920 | |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (φ6) | | Housing bore dia. (N7) | | With open ends | With closed end |
| | | min. | max. | min. | max. | | |
| — | — | 18.987 | 19.000 | 26.972 | 26.993 | 30 | — |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952470740 |
| Inside diameter | 19 mm |
| Outside diameter | 27 mm |
| Thickness | 20 mm |
| Weight | 30 g |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE