


Needle roller bearing 20MM2620-JTEKT - 20MM2620-JTEKT

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/20mm2620-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | Bearing No. ²⁾ |
|--------------------------|-----|-----|-------------------------|-------|--------------------------------------|---|
| F_w | D | C | b min. | C_0 | Oil lub. | Caged type With open ends With closed end |
| 20 | 26 | 20 | 17.2 | 18.8 | 42.5 | 6 300 |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|--------------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (F6) min. | max. | Housing bore dia. (N7) min. | max. | With open ends | With closed end |
| 20MM2620 | | 19.987 | 20.000 | 25.972 | 25.993 | 26 | 30 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952470870 |
| Inside diameter | 20 mm |
| Outside diameter | 26 mm |
| Thickness | 20 mm |
| Weight | 30 g |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE