

## Needle roller bearing 22MKM2820-JTEKT - 22MKM2820-JTEKT

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/22mkm2820-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>2)</sup>	
$F_w$	$D$	$C$	$b$ min.	$C_r$	$C_{0r}$	Oil lub.	Caged type	
22	28	20	17.3	14.9	26.5	17 000	With open ends	With closed end
								<b>22MKM2820</b>

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (H6) min.	max.	Housing bore dia. (H7) min.	max.	With open ends	With closed end
—	—	21.987	22.000	27.972	27.993	25	28

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952471167
Inside diameter	22 mm
Outside diameter	28 mm
Thickness	20 mm
Weight	28 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE