


## Needle roller bearing MKM2512-JTEKT - MKM2512-JTEKT

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/mkm2512-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_r$	$C_{0r}$	Oil lub.	Caged type With open ends    With closed end
25	32	12	9.3	9.05	12.4	14 000	<b>MKM2512</b>

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	24.987	25.000	31.967	31.992	19	21

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952471334
Inside diameter	25 mm
Outside diameter	32 mm
Thickness	12 mm
Weight	21 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE