

Needle roller bearing BHTM2525-JTEKT - BHTM2525-JTEKT

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/bhtm2525-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)	Bearing No. ²⁾
F_w	D	C	b min.	C_r	C_{0r}	Oil lub.	Caged type With open ends With closed end
25	33	25	—	24.5	40.6	14 000	BHTM2525

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	24.987	25.000	32.967	32.992	46	—

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952471495
Inside diameter	25 mm
Inside diameter	0.984" inch
Outside diameter	33 mm
Outside diameter	1.299" inch
Thickness	25 mm
Thickness	0.984" inch
Weight	46 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE