

## Needle roller bearing BTM263316A-JTEKT - BTM263316A-JTEKT

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/btm263316a-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_r$	$C_{0r}$	Oil lub.	Caged type With open ends    With closed end
25.80	33	16	—	14.2	22.4	14 000	<b>BTM263316A</b>

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	25.787	25.800	32.967	32.992	28	—

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952471549
Inside diameter	25.8 mm
Outside diameter	33 mm
Thickness	16 mm
Weight	28 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE