

## Needle roller bearing BHTM2620A-JTEKT - BHTM2620A-JTEKT

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/bhtm2620a-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
F <sub>w</sub>	D	C	b min.	C <sub>10</sub>	C <sub>90</sub>	Oil lub.	Caged type With open ends    With closed end
26	34	20	17.3	20.0	31.6	14 000	BHTM2620A

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	25.987	26.000	33.967	33.992	38	43

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250003196
Inside diameter	26 mm
Inside diameter	1.024" inch
Outside diameter	34 mm
Outside diameter	1.339" inch
Thickness	20 mm
Thickness	0.787" inch
Weight	38 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE