

## Needle roller bearing 28MKM3520-JTEKT - 28MKM3520-JTEKT

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/28mkm3520-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>	
$F_w$	$D$	$C$	$b$ min.	$C_0$	Oil lub.	Caged type With open ends    With closed end	
28	35	20	17.3	19.0	33.1	13 000	<b>28MKM3520</b>

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	27.987	28.000	34.967	34.992	35	39

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952471709
Inside diameter	28 mm
Outside diameter	35 mm
Thickness	20 mm
Weight	39 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE