

## Needle roller bearing BHTM3025-1-JTEKT - BHTM3025-1-JTEKT

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/bhtm3025-1-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>	
F <sub>w</sub>	D	C	b min.	C <sub>r</sub>	C <sub>10r</sub>	Oil lub.	
30	40	25	—	29.4	46.5	12 000	BHTM3025-1

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	29.987	30.000	39.967	39.992	69	—

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250003226
Inside diameter	30 mm
Outside diameter	40 mm
Thickness	25 mm
Weight	69 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE