

Needle roller bearing BHTM3220A-JTEKT - BHTM3220A-JTEKT

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/bhtm3220a-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min ⁻¹)	Bearing No. ²⁾
F_w	D	C	b min.	C_0	C_{10}	Oil lub.
32	42	20	17.3	23.4	34.8	11 000
						Caged type With open ends With closed end BHTM3220A

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (F6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	31.984	32.000	41.989 ⁽⁴⁾	42.014 ⁽⁴⁾	57	64

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250003233
Inside diameter	32 mm
Outside diameter	42 mm
Thickness	20 mm
Weight	57 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE