

Needle roller bearing BTM667216J-JTEKT - BTM667216J-JTEKT

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/btm667216j-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | Bearing No. ²⁾ | |
|--------------------------|----|----|-------------------------|----------------|--------------------------------------|----------|---------------------------|-----------------|
| F _w | D | C | b min. | C _r | C _{0r} | Oil lub. | Caged type | |
| | | | | | | | With open ends | With closed end |
| 66 | 72 | 16 | — | 21.9 | 61.1 | 5 900 | BTM667216J | |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (φ6) | | Housing bore dia. (N7) | | With open ends | With closed end |
| | | min. | max. | min. | max. | | |
| — | — | 65.981 | 66.000 | 71.961 | 71.991 | 54 | — |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952473024 |
| Inside diameter | 66 mm |
| Outside diameter | 72 mm |
| Thickness | 16 mm |
| Weight | 54 g |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE