


## Roller bearing NN3024K-JTEKT - NN3024K-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/roller/nn3024k-jtekt>

### Double-row cylindrical roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )		Bearing No.		
<i>d</i>	<i>D</i>	<i>B</i>	<i>r</i> min.	<i>F<sub>w</sub></i>	<i>E<sub>a</sub></i>	<i>C<sub>10</sub></i>	<i>C<sub>09</sub></i>	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore
120	180	46	2	—	165	232	392	3 200	3 900	—	—
						Mounting dimensions (mm)			(Refer.) Mass (kg)		
				<i>d<sub>a</sub></i>	<i>d<sub>a</sub></i>	<i>D<sub>a</sub></i>	<i>r<sub>a</sub></i>			Cylindrical bore	Tapered bore
				min.	max.	min.	max.			4.00	3.87
				129	—	—	171	167	2		

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952473109
Inside diameter	120 mm
Inside diameter	4.724" inch
Outside diameter	180 mm
Outside diameter	7.087" inch
Thickness	46 mm
Thickness	1.811" inch
Weight	3870 g
Packaging	1
Standard	No standard

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE