


## Roller bearing NN3036K-JTEKT - NN3036K-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/roller/nn3036k-jtekt>

### Double-row cylindrical roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )		Bearing No.		
<i>d</i>	<i>D</i>	<i>B</i>	<i>r</i> min.	<i>F<sub>w</sub></i>	<i>E<sub>a</sub></i>	<i>C</i>	<i>C<sub>07</sub></i>	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore
180	280	74	2.1	—	255	561	958	2 000	2 400		<b>NN3036K</b>

		Mounting dimensions (mm)						(Refer.) Mass (kg)	
Cylindrical bore	Tapered bore	<i>d<sub>a</sub></i>		<i>D<sub>a</sub></i>		<i>r<sub>a</sub></i>		Cylindrical bore	Tapered bore
		min.	max.	min.	max.	min.	max.		
		191	—	—	269	257	2	16.8	16.3

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952473345
Inside diameter	180 mm
Inside diameter	7.087" inch
Outside diameter	280 mm
Outside diameter	11.024" inch
Thickness	74 mm
Thickness	2.913" inch
Weight	16300 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE