

## Roller bearing NNU4944-JTEKT - NNU4944-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/roller/nnu4944-jtekt>

### Double-row cylindrical roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )		Bearing No.		
<i>d</i>	<i>D</i>	<i>B</i>	<i>r</i> min.	<i>F<sub>w</sub></i>	<i>E<sub>a</sub></i>	<i>C<sub>10</sub></i>	<i>C<sub>02</sub></i>	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore
220	300	80	2.1	244	—	501	1 220	1 700	2 000		

  

		Mounting dimensions (mm)						(Refer.) Mass (kg)		
Cylindrical bore	NNU Tapered bore	<i>d<sub>a</sub></i>		<i>d<sub>b</sub></i>		<i>D<sub>s</sub></i>	<i>r<sub>s</sub></i>		Cylindrical bore	Tapered bore
		min.	max.	min.	max.	min.	max.			
	<b>NNU4944</b>	231	241	248	289	—	2	16.7	16.0	

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952473437
Inside diameter	220 mm
Outside diameter	300 mm
Thickness	80 mm
Weight	16700 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE