


Roller bearing NN3012K-JTEKT - NN3012K-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/roller/nn3012k-jtekt>

Double-row cylindrical roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min ⁻¹)		Bearing No.		
<i>d</i>	<i>D</i>	<i>B</i>	<i>r</i> min.	<i>F_w</i>	<i>E_s</i>	<i>C</i>	<i>C₀₇</i>	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore
60	95	26	1.1	—	88.1	72.8	106	6 400	7 700	—	—

Mounting dimensions (mm)		(Refer.) Mass (kg)				
<i>d_a</i> min.	<i>d_a</i> max.	<i>D_a</i> min.	<i>r_a</i> max.	Cylindrical bore	Tapered bore	
66.5	—	88.5	87	1	0.685	0.664

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952473680
Inside diameter	60 mm
Inside diameter	2.362" inch
Outside diameter	95 mm
Outside diameter	3.74" inch
Thickness	26 mm
Thickness	1.024" inch
Weight	664 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE