


Roller bearing NN3017K-JTEKT - NN3017K-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/roller/nn3017k-jtekt>

Double-row cylindrical roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min ⁻¹)		Bearing No.		
<i>d</i>	<i>D</i>	<i>B</i>	<i>r</i> min.	<i>F_w</i>	<i>E_a</i>	<i>C</i>	<i>C₀₂</i>	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore
85	130	34	1.1	—	118	121	194	4 600	5 500	—	—

		Mounting dimensions (mm)						(Refer.) Mass (kg)	
Cylindrical bore	Tapered bore	<i>d_a</i>		<i>D_{sa}</i>		<i>r_s</i>		Cylindrical bore	Tapered bore
		min.	max.	min.	max.	min.	max.		
		91.5	—	—	123.5	119	1	1.63	1.58

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952473772
Inside diameter	85 mm
Outside diameter	130 mm
Thickness	34 mm
Weight	1580 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE