

# Needle roller bearing 20NQ2717-JTEKT - 20NQ2717-JTEKT

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/20nq2717-jtekt>

Machined ring needle roller bearings **Koyo**  
F<sub>W</sub> 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
F <sub>c</sub>	d	D	B	C <sub>r</sub>	C <sub>10</sub>	Oil lub.	Without inner ring	
20	—	27	17	0.5	14.7	20.4	22 000	<b>20NQ2717</b>
		Mounting dimensions (mm)			Weight (kg)		Applicable inner ring No.	
		d <sub>a</sub>	D <sub>a</sub>	r <sub>a</sub>	Without inner ring	With inner ring		
		—	25	0.3	0.024	—	—	

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952477398
Inside diameter	20 mm
Outside diameter	27 mm
Thickness	17 mm
Weight	24 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE