

Needle roller bearing 20NQ3020-JTEKT - 20NQ3020-JTEKT

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/20nq3020-jtekt>

Machined ring needle roller bearings Koyo
 F_w 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F_w	d	D	B	C_r	C_{10}	C_{10}	Oil lub.	Without inner ring	
20	—	30	20	—	19.8	26.4	22 000	20NQ3020	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				Without inner ring	With inner ring				
	d_a	D_a	r_a	—	—				
	max.	max.	max.	28	0.3				
					0.048				

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952477459
Inside diameter	20 mm
Outside diameter	30 mm
Thickness	20 mm
Weight	48 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE