

## Needle roller bearing NQ203218-JTEKT - NQ203218-JTEKT

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/nq203218-jtekt>

Machined ring needle roller bearings Koyo  
F<sub>W</sub> 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
F <sub>w</sub>	d	D	B	C <sub>r</sub>	C <sub>10</sub>	C <sub>10r</sub>	Oil lub.	Without inner ring	
20	—	32	18	—	21.0	26.1	21 000	<b>NQ203218</b>	
Mounting dimensions (mm)				Inner Mass (kg)		Outer Mass (kg)		Applicable inner ring No.	
With inner ring				Without inner ring	With inner ring	Without inner ring		—	
d <sub>a</sub>				0.3	—	0.053		—	
D <sub>a</sub>				—	—	—		—	
r <sub>a</sub>				—	—	—		—	

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952477466
Inside diameter	20 mm
Outside diameter	32 mm
Thickness	18 mm
Weight	53 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE