

Needle roller bearing 12NQ2410A-JTEKT - 12NQ2410A-JTEKT

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/12nq2410a-jtekt>

Machined ring needle roller bearings **Koyo**

F_w 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F_w	d	D	B	C_r	C_{10}	Oil lub.		Without inner ring	
12	—	24	9.8	—	5.9	6.3	35 000	12NQ2410A	
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
		d_a	D_a	r_a	Without inner ring	With inner ring			
		max.	max.	max.	—	—			
		—	22	0.3	0.023	—			

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250086960
Inside diameter	12 mm
Outside diameter	24 mm
Thickness	9.8 mm
Weight	23 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE