

## Needle roller bearing 16NQ2316-JTEKT - 16NQ2316-JTEKT

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/16nq2316-jtekt>

Machined ring needle roller bearings Koyo  
F<sub>W</sub> 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No. Without inner ring
F <sub>w</sub>	d	D	B	C <sub>r</sub>	C <sub>10r</sub>	Oil lub.		
16	—	23	16	0.5	13.1	16.4	27 000	<b>16NQ2316</b>
		Mounting dimensions (mm)			Weight (kg)		Applicable inner ring No.	
		d <sub>1</sub>	D <sub>1</sub>	r <sub>1</sub>	Without inner ring	With inner ring		
		min.	max.	max.	—	—		
		—	20	0.5	0.016	—		

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3616060465511
Inside diameter	16 mm
Outside diameter	23 mm
Thickness	16 mm
Weight	18 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE