

## Needle roller bearing NA5903-JTEKT - NA5903-JTEKT

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/na5903-jtekt>

Machined ring needle roller bearings Koyo  
 $F_w$  29 – 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
$F_w$	$d$	$D$	$B$	$B_1$	$C_r$	$C_{10}$	Oil lub.		Without inner ring
22	17	30	18	—	0.9	15.2	21.9	20 000	—
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
		With inner ring	$d_a$ min.	$D_a$ max.	$r_a$ max.	Without inner ring	With inner ring		
		NA5903	19	28	0.3	0.031	0.052	IRM172218	

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3616060465542
Inside diameter	17 mm
Outside diameter	30 mm
Thickness	18 mm
Weight	52 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE