


Needle roller bearing NA4900UU-JTEKT - NA4900UU-JTEKT

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/na4900uu-jtekt>

Machined ring needle roller bearings Koyo
F_W 29 – 37 mm

With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No. Without inner ring	
F _w	d	D	B	C _r	C _{10r}	Oil lub.			
14	10	22	13	7.5	7.7	14 000	—	—	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				d ₁ min.	D ₁ max.	r ₁ max.	Without inner ring	With inner ring	
NA4900UU				12	20	0.3	—	0.025	IRM101414

[Note] 1) Limiting speeds of bearing number NA49...UU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952477770
Inside diameter	10 mm
Outside diameter	22 mm
Thickness	13 mm
Weight	25 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE