


Needle roller bearing NA4901UU-JTEKT - NA4901UU-JTEKT

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/needle/na4901uu-jtekt>

Machined ring needle roller bearings Koyo

F_w 29 ~ 37 mm

With inner ring



F_w	Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No. Without inner ring
	d	D	B	B ₁	C _r	C _{10r}	Oil lub.		
16	12	24	13	14	8.3	9.2	12 000	—	—
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
		With inner ring			Without inner ring	With inner ring			
		d_a	D_a	r_a	—	0.028	IRM121614		
		min.	max.	max.					
		NA4901UU	14	22	0.3				

[Note] 1) Limiting speeds of bearing number NA49...UU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952477800
Inside diameter	12 mm
Inside diameter	0.472" inch
Outside diameter	24 mm
Outside diameter	0.945" inch
Thickness	13 mm
Thickness	0.512" inch
Weight	28 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE