


## Tapered roller bearing 462-500-JTEKT - 462-500-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/462-500-jtekt>

Double-row tapered roller bearings Koyo  
TDO type



Boundary dimensions (mm)						Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	C	r <sub>1</sub> min.	r <sub>1</sub> max.	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.
500	720	167	149	6	3	2 580	5 690	250	330

Bearing No.	Mounting dimensions (mm)					Constant e	Axial load factors			Refer.) Mass (kg)
	d <sub>4</sub> min.	D <sub>4</sub> min.	S <sub>4</sub> min.	r <sub>4</sub> max.	r <sub>5</sub> max.		Y <sub>2</sub>	Y <sub>3</sub>	Y <sub>0</sub>	
462/500	528	679	9	5	2.5	0.40	1.71	2.54	1.67	210

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952481692
Inside diameter	500 mm
Outside diameter	720 mm
Thickness	149 mm
2nd Thickness	167 mm
Weight	210000 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE