


## Tapered roller bearing 45332-JTEKT - 45332-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/45332-jtekt>

Double-row tapered roller bearings  
TDI type Koyo



Boundary dimensions (mm)						Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>B</i>	<i>T</i>	<i>r</i> max.	<i>r</i> min.	<i>C<sub>r</sub></i>	<i>C<sub>0r</sub></i>	Grease lub.	Oil lub.
160	270	86	86	2.5	3	678	1100	1000	1400

Bearing No.	Mounting dimensions (mm)						Con- stant <i>e</i>	Axial load factors			(Refer.) Mass (kg)
	<i>d<sub>a</sub></i> max.	<i>D<sub>a</sub></i> max.	<i>D<sub>a</sub></i> min.	<i>S<sub>a</sub></i> min.	<i>r<sub>a</sub></i> max.	<i>r<sub>b</sub></i> max.		<i>Y<sub>2</sub></i>	<i>Y<sub>3</sub></i>	<i>Y<sub>0</sub></i>	
45332	193	258	237	4	2	2.5	0.35	1.95	2.90	1.91	19.8

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952481845
Inside diameter	160 mm
Outside diameter	270 mm
Thickness	86 mm
Weight	19800 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE