

## Tapered roller bearing 45338-JTEKT - 45338-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/45338-jtekt>

Double-row tapered roller bearings **Koyo**  
TDI type



Boundary dimensions (mm)						Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	B	T	r	r <sub>1</sub>	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.
190	320	104	104	3	4	981	1 590	840	1 100

  

Bearing No.	Mounting dimensions (mm)						Con- stant e	Axial load factors			(Refer.) Mass (kg)
	d <sub>2</sub> max.	D <sub>2</sub> max.	D <sub>2</sub> min.	S <sub>2</sub> min.	r <sub>2</sub> max.	r <sub>2</sub> min.		Y <sub>2</sub>	Y <sub>3</sub>	Y <sub>0</sub>	
45338	224	306	280	5	2.5	3	0.35	1.95	2.90	1.91	34.0

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952481906
Inside diameter	190 mm
Outside diameter	320 mm
Thickness	104 mm
Weight	34000 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE