


## Tapered roller bearing 45264-JTEKT - 45264-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/45264-jtekt>

Double-row tapered roller bearings — Koyo  
TDI type



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		
<i>d</i>	<i>D</i>	<i>B</i>	<i>T</i>	<i>r</i> max.	<i>r</i> min.	<i>C<sub>r</sub></i>	<i>C<sub>0r</sub></i>	Grease lub.	Oil lub.
320	480	121	121	4	5	1 630	3 180	470	630

Bearing No.	Mounting dimensions (mm)						Con- stant <i>e</i>	Axial load factors			(Refer.) Mass (kg)
	<i>d<sub>a</sub></i> max.	<i>D<sub>a</sub></i> max.	<i>D<sub>a</sub></i> min.	<i>S<sub>a</sub></i> min.	<i>r<sub>a</sub></i> max.	<i>r<sub>b</sub></i> max.		<i>Y<sub>2</sub></i>	<i>Y<sub>3</sub></i>	<i>Y<sub>0</sub></i>	
45264	368	462	434	6	3	4	0.26	2.55	3.80	2.50	77.8

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952482040
Inside diameter	320 mm
Outside diameter	480 mm
Thickness	121 mm
Weight	77800 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE