


## Tapered roller bearing 45284-JTEKT - 45284-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/tapered/45284-jtekt>

Double-row tapered roller bearings TDI type Koyo



Boundary dimensions (mm)						Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>B</i>	<i>T</i>	<i>r</i> max.	<i>r</i> min.	<i>C<sub>r</sub></i>	<i>C<sub>0r</sub></i>	Grease lub.	Oil lub.
420	620	150	150	5	6	2 800	5 200	320	430

Bearing No.	Mounting dimensions (mm)					Con- stant <i>e</i>	Axial load factors			(Refer.) Mass (kg)	
	<i>d<sub>a</sub></i> max.	<i>D<sub>a</sub></i> max.	<i>D<sub>a</sub></i> min.	<i>S<sub>a</sub></i> min.	<i>r<sub>a</sub></i> max.		<i>Y<sub>2</sub></i>	<i>Y<sub>3</sub></i>	<i>Y<sub>0</sub></i>		
45284	475	598	564	6	4	5	0.33	2.03	3.02	1.98	152

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250130533
Inside diameter	420 mm
Inside diameter	16.535" inch
Outside diameter	620 mm
Outside diameter	24.409" inch
Thickness	150 mm
Thickness	5.906" inch
Weight	152000 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE