

Roller bearing NQ24-16-JTEKT - NQ24-16-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/roller/nq24-16-jtekt>

Machined ring needle roller bearings ————— **Koyo**
F_W 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	C _r	C _{0r}	Oil lub.		Without inner ring	
24	20	32	16	0.3	13.4	22.2	19 000	NQ24/16	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				Without inner ring	With inner ring				
	d ₁ min.	D ₁ max.	r _s max.	0.035	0.052				
	22	30	0.3						

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952482316
Inside diameter	24 mm
Inside diameter	0.945" inch
Outside diameter	32 mm
Outside diameter	1.26" inch
Thickness	16 mm
Thickness	0.63" inch
Weight	35 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE