

## Roller bearing NQ25-16-JTEKT - NQ25-16-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/roller/nq25-16-jtekt>

### Machined ring needle roller bearings Koyo

$F_w$  29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
$F_w$	$d$	$D$	$B$	$C_r$	$C_{10}$	$C_{10}$	Oil lub.	Without inner ring	
25	—	33	16	—	14.1	20.6	18 000	NQ25/16	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				Without inner ring	With inner ring				
	$d_a$	$D_a$	$r_a$	—	—				
	max.	max.	max.	—	—				
	—	31	0.3	0.034	—				

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952482354
Inside diameter	25 mm
Outside diameter	33 mm
Thickness	16 mm
Weight	34 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE