

Roller bearing NQ29-30-JTEKT - NQ29-30-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/roller/nq29-30-jtekt>

Machined ring needle roller bearings ————— **Koyo**
F_W 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.		
F _w	d	D	B	B ₁	C _r	C ₁₀	Oil lub.	Grease lub.	Without inner ring	With inner ring	
29	25	38	30	—	28.9	54.3	16 000	—	NQ29/30	—	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.					
With inner ring				d ₂ min.	D ₂ max.	r _a max.	Without inner ring	With inner ring			
				27	36	0.3	0.085	0.125			

[Note] 1) Limiting speeds of bearing number NA49..LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952482620
Inside diameter	29 mm
Outside diameter	38 mm
Thickness	30 mm
Weight	85 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE