


## Roller bearing NA4905UU-JTEKT - NA4905UU-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/roller/na4905uu-jtekt>

Machined ring needle roller bearings Koyo  
 $F_w$  29 – 37 mm

With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
$F_w$	$d$	$D$	$B$	$C_r$	$C_{10}$	Oil lub.	Grease lub.	Without inner ring	
30	25	42	17	18.4	22.4	6 800	—	—	
Mounting dimensions (mm)				Mass (kg)		Applicable inner ring No.			
With inner ring				Without inner ring	With inner ring	—			
NA4905UU				27	40	0.3	—	0.092	IRM253018

[Note] 1) Limiting speeds of bearing number NA49...UU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952482668
Inside diameter	25 mm
Outside diameter	42 mm
Thickness	17 mm
Weight	92 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE