


## Roller bearing NA4905R-JTEKT - NA4905R-JTEKT

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/roller/na4905r-jtekt>

### Machined ring needle roller bearings Koyo

$F_w$  29 ~ 37 mm

With inner ring



| Boundary dimensions (mm) |     |     |     | Basic load ratings (kN) |                 | Limiting speeds <sup>1)</sup> (min <sup>-1</sup> ) |                    | Bearing No. |
|--------------------------|-----|-----|-----|-------------------------|-----------------|--|--------------------|-------------|
| $F_w$                    | $d$ | $D$ | $B$ | $C_r$                   | $C_{10}$        | Oil lub.   | Without inner ring |             |
| 30                       | 25  | 42  | 17  | 24.2                    | 31.7            | 15 000   | —                  |             |
| Mounting dimensions (mm) |     |     |     | Reference Mass (kg)     |                 | Reference Applicable inner ring No.                |                    |             |
| With inner ring          |     |     |     | Without inner ring      | With inner ring |  |                    |             |
| <b>NA4905R</b>           |     |     |     | 0.085                   | 0.092           | IRM253017  |                    |             |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCT FEATURES

|                  |               |
|------------------|---------------|
| Brand            | JTEKT         |
| N° Ean13         | 3663952482705 |
| Inside diameter  | 25 mm         |
| Outside diameter | 42 mm         |
| Thickness        | 17 mm         |
| Weight           | 92 g          |
| Packaging        | 1             |

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE